

DRILL SCREW PILOT HOLES  
(Ø0.285") IN RAIL AS REQUIRED.  
USE LOAD BAR AS TEMPLATE.

REMOVE CONCRETE  
ANCHOR AS REQUIRED

THREAD FORMING  
SCREWS  
(TYP 2 PLACES)

LOAD BAR

EXPLODED VIEW

LOCATE TEE AS REQUIRED  
ALONG RAIL. AVOID  
REMOVABLE PIN/LEG  
BRACKETS.

ASSEMBLED VIEW

REV	DESCRIPTION	BY	CHKD	DATE
-----	-------------	----	------	------

**ABT, INC.**  
P.O. BOX 837 / 259 MURDOCK ROAD  
TROUTMAN, NC 28166  
(704) 528-9806 (800) 438-6057  
www.abtdrains.com

FABRICATION DRAWING © 2007 ABT, Inc.  
**TRENCH FORMER DETAIL  
TEE USING AUXILIARY RAIL**

FILE: **DET-G3-TEE-00**      PART: **DET-G3-TEE**

Proprietary rights of ABT, Inc. are included in the information disclosed herein. The recipient, by accepting this document, agrees that neither this document nor the information disclosed herein nor any part thereof shall be copied, reproduced or transferred to others for manufacturing or for any other purpose except as specifically authorized in writing by ABT, Inc.

**DISCLAIMER:** The customer and the customer's architects, engineers, consultants and other professionals are completely responsible for the selection, installation, and maintenance of any product purchased from ABT, and EXCEPT AS EXPRESSLY PROVIDED IN ABT'S STANDARD WARRANTIES, ABT MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR THE CUSTOMER'S APPLICATION. Copies of ABT's standard warranties are available upon request.